

Cable Glands : Type CW


Application :

In outdoor areas with armoured or braided cable, including lead sheathed.

Function :

All glands offer clamping of the armour or braid and a weather seal to the outer sheath of the cable.

- Standard** : BS 6121, Part 1:1989
Mechanical : Provides retention of armour or braid impact resistant
Size : CW 20S - 90L
Material : Brass / Aluminium
Finish : Matt / Nickel
Gasket : Neoprene
Shrouds : Pvc / Lsf
Kits : CW Gland, Shrouds, Locknut and Earth tag



CW TYPE GLAND SPECIFICATIONS							
GLAND SIZE	Entry Threads		Cable Acceptance Details		Hexagonal Details		PVC
	Dia	Length	Dia	Dia	A/F	A/C	Shroud Size
	N'	D'	A'	B'	F'	C'	
CW-20S	20	15	11.80	17.80	24.00	27.00	20S
CW-20L	20	15	15.00	20.80	27.70	31.00	20
CW-25S	25	15	17.60	24.00	31.50	35.00	25
CW-25L	25	15	20.00	27.40	35.00	39.00	25
CW-32S	32	15	25.70	32.20	43.00	47.50	32
CW-32L	32	15	26.00	34.20	43.00	47.50	32
CW-40S	40	20	30.40	38.00	51.50	57.00	40
CW-40L	40	20	33.20	40.50	51.50	57.00	40
CW-50S	50	20	39.70	47.00	58.50	65.00	50
CW-50L	50	20	43.50	54.00	66.00	73.00	50
CW-63S	63	20	51.50	61.00	72.00	80.00	63
CW-63L	63	20	55.00	66.00	80.00	89.00	63
CW-75S	75	20	62.50	74.50	86.50	97.00	75
CW-75L	75	20	67.80	77.50	94.00	105.00	75
CW-90	90	20	84.00	96.00	106.00	118.00	90

Also Available
Without Armour Ring
With Knurling Inside