


**Cable Glands : Type BW**

**Application :**

In indoor areas with armoured or braided cable, including lead sheathed.

**Function :**

All glands offer clamping of the armour or braided.



- Standard** : Bs 6121, Part 1:1989
- Mechanical** : Provides retention of armour or braid
- Size** : BW 20s - 90L
- Material** : Brass / Aluminium
- Finish** : Matt / Nickel
- Shrouds** : Pvc / Lsf
- Kits** : BW Gland, Pvc Shrouds, Locknut and Earth tag



BW TYPE GLAND SPECIFICATIONS							
GLAND SIZE	Entry Threads		Cable Acceptance Details		Hexagonal Details		PVC
	Dia	Length	Dia	Dia	A/F	A/C	Shroud
	'N'	'D'	'A'	'B'	'F'	'C'	Size
BW-20S	20	15	10	11.50	22.0	24.0	20S
BW-20L	20	15	10	14.30	25.0	28.0	20
BW-25S	25	15	10	16.20	31.0	34.0	25
BW-25L	25	15	10	21.00	34.0	38.0	25
BW-32S	32	15	10	25.70	35.0	40.0	32
BW-32L	32	15	10	25.50	40.0	45.0	32
BW-40S	40	20	15	30.20	48.0	54.0	40
BW-40L	40	20	15	32.20	49.0	55.0	40
BW-50S	50	20	15	39.70	57.0	63.0	50
BW-50L	50	20	15	43.50	61.0	68.0	50
BW-63S	63	20	15	50.00	68.00	76.00	63
BW-63L	63	20	15	55.00	74.0	83.0	63
BW-75S	75	20	15	62.00	83.00	88.00	75
BW-75L	75	20	15	67.20	89.0	100.0	75
BW-90	90	20	20	84.00	100.00	110.0	90